

Ref: CA/SCM/OT/75/2023-2024

11th April, 2024

Addendum No. 1

To All Bidders,

REF: OPEN NATIONAL TENDER FOR REPAIR AND EXTENSION OF PUBLIC ADDRESS SYSTEM AT CA CENTER AND CA OLD BUILDING BLOCK CA/SCM/OT/75/2023-2024

Please refer to the above-mentioned Tender that appeared in MY GOV on 19th March 2024.

Pursuant to Section 75 of the Public Procurement and Asset Disposal Act, 2015 and clause 7.1 of the Tender document uploaded to our website, and the Supplier's Portal, the Authority wishes to amend the Tender Document as follows: -

Technical specifications

No.	Item	Description	CA Response/Amendment
1.	ITC Mixer Amplifier	T-60DTB * Standard rack mounted design (1U), exquisite SMT process design. * With MP3 function module, adopt LCD display, support playback of various file formats in USB disk such as MP3, WMA, APE, FLAC, WAV, and AAC; with TF card, support mobile phone Bluetooth function, and can display song names. * Support mp3/TUNER/Bluetooth remote control function. * 1 channel EMC input, 2 channel AUX input, 4 channel MIC input. * Channel priority function EMC>MIC1>MIC2, MIC3, AUX1, AUX2. * Each input has independent volume adjustment, and the total volume has treble, bass adjustment and volume control function. * The device is equipped with level indication, overload and protection indicators. * The device has good self-protection such as short circuit, overload and overheating. * Two output modes: constant voltage output 100V, constant resistance output 4-16Ω. * The high-efficiency energy-saving switching power supply is perfectly combined with the high-energy saving and ultra-stable design of class D digital power amplifier. * Wide voltage supply: 180V-240V can work normally. * Standby power supply 24V switching without delay (optional).	ITC Mixer Amplifier or Equivalent
2.	I2TC Speaker	T-206A	I2TC Speaker or

No.	Item	Description	CA Response/Amendment
			Equivalent
3.	C3 able	Speaker cable	No change
4.	C4 able	CAT 6 outdoor cable	No change
5.	K5 ramer Audio Embedder	Max Data Rate — 8.91Gbps (2.97Gbps per data channel) 4K@60Hz (4:2:0) UHD, 4Kx2K support Kramer Equalization & re-Klocking™ Technology	K5 ramer Audio Embedder or Equivalent
6.	K6 ramer Transmitter	HDMI HDBaseT 4K/60 UHD (4:2:0) HDCP 2.2 compatible HDCP Compliant	K6 ramer Transmitter or Equivalent.
7.	K7 ramer Receiver	Maximum data rate 10.2 Gb/s (3.4 Gb/s per graphic channel) HDTV compatible HDCP compliance HDBaseT technology 3D pass-through 2K and 4K support System range up to 230' (70m) Status LEDs for input, output, link, and power	K7 ramer Receiver or Equivalent
8.	K8 ramer Audio De-Embedder	4K HDR HDMI Audio De-embedder Max. Data Rate — 18Gbps Deep Color up to 12-bit De-embed from the HDMI output or ARC Output to digital or analog Audio Smart EDID Management	K8 ramer Audio De-Embedder or equivalent
9.	K9 ramer HDMI Cable	Kramer C-HM/HM High Speed HDMI Cable 10.7m	K9 ramer HDMI Cable or Equivalent
10	UPS	Smart UPS – 5 KVA	No change

The tender closing date has been extended to 12th April 2024 at 10.30 am.



Peter Mwangi
FOR: DIRECTOR GENERAL